HD18 HIWF-402C | M18™ impact wrench with friction ring

- Engineered for heavy use, the M18™ impact wrench with friction ring delivers maximum cordless power on the jobsite.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- With its Milwaukee® 4-pole frameless motor it delivers a staggering 610 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- ½″ square friction ring.
- Ideal for heavy applications such as steel fabrication, mechanical fastening, industrial construction and automotive work.
- Light weight and ergonomically designed.

	HD18 HIWF-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Charger supplied	80 min
Impact rate (ipm)	0 - 2200
Max. torque (Nm)	610
No load speed (rpm)	0 - 1900
No. of batteries supplied	2
Sound power level (dB(A))	91
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	80
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration screw driving (m/s²)	11.3
Vibration screw driving uncertainty (m/s²)	1.5
Voltage (V)	18
Weight with battery pack (kg)	3.0