PLH 32 XE | 32 mm SDS-plus 3-mode L-shaped hammer

- Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 3.8 joule single blow energy.
- 900 watt motor combined with optimised drilling speed results in unsurpassed drilling performance.
- Electronics with accelerator switch.
- Good balance and easy handling from the compact L-shape design with AVS (Anti-Vibration-System) and soft grip handle.
- Fast tool changing from the FIXTEC system with keyless chuck.
- Heavy Duty magnesium gear casing for optimum seating of gears for a longer operational life.
- Reliable safety clutch protects machine and user.

	PLH 32 XE
Blow energy (EPTA)(J)	3.8
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 800
Max. drilling concrete (mm)	32
Max. drilling masonry (mm)	32
Max. drilling steel (mm)	16
Max. drilling wood (mm)	40
Power input (W)	900
Sound power level (dB(A))	106
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	95
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Front handle with metal depth gauge, adaptor with 13 mm keyless chuck, drill bit lubricant
Supplied in	Kitbox
Vibration chiseling (m/s^2)	20
Vibration chiselling uncertainty (m/s^2)	1.5
Vibration drilling (m/s^2)	22
Vibration drilling into concrete [m|s²]	25
Vibration drilling into concrete uncertainty [m|s²]	2.3
Weight (kg)	3.6