HD18 HX-402C | M18™ 4-mode SDS-Plus hammer with FIXTEC chuck

- High powered motor gives corded tool performance.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy.

	HD18 HX-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Blow energy (EPTA)(J)	2.4
Charger supplied	80 min
Max. drilling concrete (mm)	24
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. percussion rate (bpm)	4200
No. of batteries supplied	2
Optimised drilling capacity in concrete (mm)	Ø 6 - 18
Sound power level (dB(A))	99
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	88
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle with metal depth gauge, FIXTEC adaptor chuck
Supplied in	Kitbox
Vibration chiseling (m/s²)	7.4
Vibration chiselling uncertainty (m/s²)	1.5
Vibration drilling (m/s²)	12.2
Vibration drilling into concrete [m|s²]	12.2
Vibration drilling into concrete uncertainty [m|s²]	1.5
Voltage (V)	18
Weight with battery pack (kg)	3.7