M18 BH-402C | M18™ compact 2-mode SDS-plus hammer

- Superior power to weight ratio in its class 2.5 kg 1.2 J (EPTA).
- Bright LED workspace illumination.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility.

	M18 BH-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Blow energy (EPTA)(J)	1.2
Blow energy (J)	1.2
Charger supplied	80 min
Max. drilling concrete (mm)	16
Max. drilling steel (mm)	10
Max. drilling wood (mm)	16
Max. percussion rate (bpm)	7000
No load speed (rpm)	0 - 1300
No. of batteries supplied	2
Optimised drilling capacity in concrete (mm)	Ø 5.5 - 13
Sound power level (dB(A))	98.9
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	87.9
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration drilling (m/s²)	10.3
Vibration drilling into concrete [m|s²]	10.3
Vibration drilling into concrete uncertainty [m|s²]	1.5
Voltage (V)	18
Weight with battery pack (kg)	2.5